ECOPIC COPIC

SUMMARY

- FIXNET[®] BOX
- PREDATOR[®]
- ECOPIC[®] TILE
- FILET NET
- BIRD WIRE
- · CABLE BIRD[®] WIRE
- SELFIXING[®]
- CABLE BIRD®
- BIRD-DUT®
- · ASTUCLIP KIT
- DEPIGEONAL®
- SELCLEANING[®]
- THE COMPANY







HERI

TAGE



Sortie

ABOUT

ECOPIC has

been specialised in the design, manufacture and distribution of bird deterrent systems, since 1986. The systems we use, do not cause any harm to the birds. **ECOPIC** products are designed purely to deter birds from landing on the protected surfaces.

OUALITY TRACEABILIT ISO STANDARD 9001:2015 WARRANTY

Trademarks marketed by **ECOPIC** include:

ECOPIC[®] • DEPIGEONAL[®] • BIRD-OUT[®] • CABLE BIRD[®] • FIXNET® • SELCLEANING® • FILETNET • ECOPIC® TILE •

ECOPIC is responsible for the basic design and development of all products and systems. If necessary, the systems are registered and patented. We work in close collaboration with our many partners (e.g. raw materials suppliers) and purchase all raw materials direct. This ensures total quality control and traceability which in turn ensures the highest standards of quality. All manufacturing is performed directly by ECOPIC to further guarantee the quality.

Our products are often made of stainless-steel and polycarbonate (for the « base »). The steel wire we use gives an important mechanical resistance, and is produced to a minimum performance standard of 1700-2000N/mm2. This is important since guarantees the product efficiency through what we call "spring quality wire" Standards for resistances to salty mists are also established. We use the DIN50021, NSS ASTM B117 standard, recognized and used in the automobile industry. One of our material, STEELINOX®+ passes the limit of 1000 hours of salty mists; again a unique standard of quality.

Our polycarbonate comes from worldwide, well-known manufacturers. No exotic products, are used due to our requirement for impeccable

quality. The polycarbonate we use is 80% minimum virgin polycarbonate since UV resistance is essential ; only perfect control, guarantees an optimal

The above, summarises why our products are not simply « spikes ». Everyone does not manufactures quality products.

Do not hesitate to ask for more details about the materials we use or our guarantees.

We manufacture in France where we have competent technicians, quick reaction times, a premium quality production facility and total quality control. All the above mentioned reasons enable us to offer you an unbeatable range of products.

We have many additional services to assist you : Advice for quotations Assistance marketing

Technical assistance

- Assistance for coding our products (EAN)
- A 24 hours delivery On-line systems.

We offer you much more than just a range of products.



Christophe BOYER

resistance

www.ecopic.com



ECOPIC is permanently represented in more than 38 countries. **ECOPIC** is regularly confronted with every manner of bird problems and all kinds of architectural situations. Bird management can be complex. You need to rely upon an expert.

WHY SHOULD YOU PROTECT YOUR PROPERTY AGAINST BIRDS :

1st • Aesthetics

A single pigeon, gull or starling on your buildings causes little trouble. The aesthetic problem arises when the number of birds increases. In fact as few as twenty birds on a statue, a balcony or a cornice can seriously damage the architecture.

2nd • Excretions

Bird faeces causes quite an eyesore, but more importantly it causes structural problems. Bird faeces are extremely acidic, and will chemically burn the building surfaces.

3rd • Health

The proliferation of birds generates the risk of illness through the spread of more than 60 diseases :

- · Virals infections : flu, paramixovirus...
- · Parasitics infections : teniasis, ectoparasitic infestations
- · Fungal infections.

WE HAVE IDENTIFIED SEVERAL DIFFERENT ZONES :

- Low pressure : Used for resting only.
- Medium pressure : Used for observing feeding areas (e.g. a cornice over a restaurant), sunbathing...
- High pressure zone :
- Nesting...

One or several ECOPIC products correspond to each of these zones.

Be careful, on some buildings there are zones on which few birds will land. These are usually places that are exposed to wind currents. In this case, you will rarely find pigeons, but gulls or seagulls may persist.

Careful observation is essential ; do not hesitate to contact the **ECOPIC** team. We have been the experts in bird control for more than 30 years.





Active professional cleaner. Prepares supports for bird deterrent systems like ECOPIC®, DEPIGEONAL®, BIRD-OUT®, CABLEBIRD®...





S ACTION

Used to prepare supports before installation of ECOPIC[®], DEPIGEONAL[®], BIRD-OUT[®], CABLEBIRD[®], BIRDWIRE...

Recommanded for all surfaces : stone, concrete, building façade, zinc, building cladding...

S MAIN ADVANTAGES

• Product based on natural essential oils

• Fragrance of natural essences of plants

- 1 litre can
- Professional cleaner with natural plant extracts
- Dilute in water
- The surface cleaned with 1 litre depends on the type of surface cleaned and its condition



Est.



C 07 F


SELCLEANING [®] Concentrate Product	QUANTITY OF Water to add	QUANTITY OF READY To use product
0,5 Litre	2 Litres	2,5 Litres
1 Litre	4 Litres	5 Litres
2 Litres	8 Litres	10 Litres

www.ecopic.com





www.ecopic.com



ECOPIC[®] can be fitted to all surfaces (zinc, wood, stone, reinforced, concrete, cement mortar, marble...).

Installation : optimum weather conditions • Temperatures between +5°C and +30°C, sheltered from rain.

Preparation of the surface :

- Cleaning with SELCLEANING®
- · Removal of dust, dirt and grease, drying
- If necessary, application of a primer on porous surfaces.

Simple, fast, precise fitting : • With silicone adhesive • With screws or nails.


Recommendation for optimised gluing : **SELFIXING**[®] silicone adhesive.

ECOCLIPS 3 can be fitted to all types of gutter with a rim of 12 to 30 mm (metallic or synthetic materials). • Fitting by simply clipping to the outer part of the gutter.



ecopic@ecopic.com

www.ecopic.com



www.ecopic.com







S ACTION

DEPIGEONAL[®] forms a virtually invisible protective barrier, ensuring conservation of buildings and good hygiene, as well as a free gutter flow, without harming birds.

LE ENY

S MAIN ADVANTAGES

- · Easy to fit
- Discreet
- Economical
- Reliable

- All types of building
- All types of surface
- All types of gutter

DESCRIPTION

Spikes in stainless-steel 302/ STEELINOX® / STEELINOX®+ (Ø 1,3 mm or 1,4 mm).

Manufactured using non-corroding materials. Polycarbonate base mass UV-stabilised.

DEPIGEONAL® has a 10 years warranty*.

S FITTING

DEPIGEONAL[®] can be fitted to all surfaces (zinc, wood, stone, reinforced, concrete, cement mortar, marble...).

Installation : optimum weather conditions • Temperatures between +5°C and +30°C, sheltered from rain.

Preparation of the surface :

• Cleaning with SELCLEANING®

- · Removal of dust, dirt and grease, drying
- If necessary, application of a primer on porous surfaces.

Simple, fast, precise fitting : • With silicone adhesive • With screws or nails.

Recommendation for optimised gluing : **SELFIXING**[®] silicone adhesive.


ULTRA CLIPS 3 can be fitted to all types of gutter with a rim of 12 to 30 mm (metallic or synthetic materials). • Fitting by simply clipping to the outer part of the gutter.





ecopic@ecopic.com

opic.com



ecopic@ecopic.com

www.ecopic.com





F R

for birds removal







Economical

 Easy to fit · Ready to use

ASTUCLIP Kit is an accessory

that keeps the Ultra 1 by simply clipping on the outside profile of the gutter while respecting the flow of rainwater.

Kit of 10 LM gutter protection, 32 unit of Ultra 1 with 64 clips ASTUCLIP.

Only available in kit of 10 LM Ultra 1 + 64 clips.

MAIN ADVANTAGES

PROTECTION

G E

· Half round gutters

DESCRIPTION

Suitable for bead gutter with maximum diameter :

ASTUCLIP (Ref: ECO144B): Maximum 22 mm.

ASTUCLIP has a 10 years warranty*.

FITTING

Astuclip can be fitted to half round gutters (zinc/aluminium or synthetic materials) by simply clipping on the outside profile of the gutter.

Insatallation : Optimun weather conditions • Temperatures bettween +5°C and +30°C, sheltered from rain.

Preparation of the surface :

- Cleaning with SELCLEANING®
- · Removal of dust, dirt and grease, drying

Simple, fast, precise fitting : • Apply pressure with the thumd of the hand on the clip, it is immediatly operational.

Recommendation for optimized clipping (by gluing) : SELFIXING[®] silicone adhesive.

It is recommended never to install products that could interfere with the functioning of the gutter.







COPIC

ecopic@ecopic.com

www.ecopic.com







Kit of 10 LM of Ultra 1 + 64 cl

TAGE

Astuclip kit (10 LM of gutter protection) • Packaging dimensions : 34,5 x 22 x 14,5 cm / 1.5 kg Special for gutters with a maximum diameter hem 22 mm

The kit includes :

F R


ASTUCLIP

- 64 clips Astuclips (Stainless-steel 301 grade)
- Size of the clip : width 10 mm x height 49,75 mm


ULTRA 1

- 32 units of Ultra 1
- Mass U.V. stabilised and 100% virgin polycarbonate base
 Stainless-steel 302 grade spikes STEELINOX®/ STEELINOX®+ Ø 1,3 mm
- Size of the unit : lenght 310 x width 55 x height 110 mm
- Width protected : Gutter edges
- Protection: pigeons, carrion crows and magpies

Only available in kit of 10 LM Ultra 1 + 64 clips.









Electro-vibratory deterrent system to repel birds. Recommended for all pressure zones.



SACTION

50205

BIRD-OUT[®] provides an efficient barrier to protect against birds. Its components are flexible, so they fit all architectural profiles perfectly, whilst preserving the aesthetic quality of the area to be protected.

S MAIN ADVANTAGES

· Available in Steelinox® or stainless-steel

· Can be adapted to all surfaces

· Very fast fitting

Discreet

- PROTECTION
- Sloping roofs, flat roofs
- Bridges
- Statues
- Cornices, tympanaBell towers

www.ecopic.com

- Inner courtyards
- Street-lights

DESCRIPTION

BIRD-OUT[®] uses a sequential electric generator equipped with a condenser, to produce a repellent effect that is harmless to birds, according to human standards.

- System available in Steelinox® or in stainless-steel rods Ø 2 mm, length 1 m.
- Easy to bend to follow the profile of the architecture.
- Directional changes can easily be produced using BDO clips or torsion springs.

BIRD-OUT® has a 10 years warranty* (excludes the generator).

S FITTING

BIRD-OUT[®] can be fitted to all types of surface (zinc, wood, stone...).

Installation :

 \bullet Optimum weather conditions thermal range +5° to +30° C.

Simple, fast, precise fitting:

- With silicone adhesive
- With screws or nails.

Recommendation for optimised gluing : **SELFIXING**[®] silicone adhesive.

We do not recommend fitting the supports on surfaces with easy public access (window ledges, etc.).

Installation of a warning sign is required.

MAINTENANCE MANDATORY Contact us for details





RD-OU



BDO101	Bird-out [®] Steelinox [®]	20 M kit
BDO107	Bird-out [®] Inox	20 M kit
BDO108	Bird-out [®] Evolution	20 M kit
BDO116	Bird-out [®] Evolution Inox	20 M kit

One kit includes :

- 40 bars (Ø 2mm length of 1m).
- · 40 polycarbonate supports anti-UV treated in the mass
- 2 0,50m coils of springs or BDO Clip (getting 40 connections of 2,5 cm).
- 2 triple connexions + 2 heat shrink tubing.
- Packaging dimensions : 10 x10 x 100 cm.
- · Packaging weight : 1,4 kg.
- · Widths protected : see technical specifications available on request.
- Technical sheet for fitting supplied in each pack.

🔍 МОЦИТ

REF. DESCRIPTION PACKAGING BDO012 Mount Unit

- · Multi-surface mounting and multi-directional positioning, manufactured in UV-stabilised polycarbonate.
- · Anti-arcing safety system. Water repellent system.

Historical monuments require 3 mounts per metre.

🔍 BAR



- Bar made of Steelinox[®] or stainless-steel Ø 2 mm
- · length 1 m.
- · Can easily be cut to the required length or bent to follow the profile of the architecture.

🔍 SPRING



🍋 BDO CLIP



- · Length : 40 mm.
- Width : 6 mm.
- The clip ensures perfect fixing of the rods akin to a « welding process », while still facilitating directional changes without strain or pressure.





• To connect the EVO100 cable to the bars

- Standard EN50143.
- · Heat shrink tubing (black or white)



38 mm





ACCESSORIES

Polycarbonate support posts allow multiple strands and multiple directions. UV resistant.

Spring or BDO Clip

3 points locking system for better conductivity

3 points locking system

prevent water ingress

Breakable part

DOUBLE CABLE

Ref.: EVO100

Description : Bird-out® double cable

Packaging : Spool of 50 M

• To safely connect two spaced locations of the BIRD-OUT® circuit.

 Double cable with RZ flame retardant PVC sheath and multi-wire copper conductive material

· Light gray color, it has a black sheath and another red to locate the side ⊕ ideal when going through a chute.

Standard IEC 60228 and IEC 20-22 II



SENERATOR

Ref.: EVO050

Description : Central generator 02 Packaging : Unit

• 220 volts generator.

 Technical specifications on request.





PRDT ЕСТ YDUR HERITAGE



Deterrent spikes to repel birds. Recommended for low medium and strong bird pressures.







The dual action of CABLE BIRD® rods prevents pigeons from settling on buildings ledges.

When the bird attempts to land, the rod rotates (ECOPIC patent) and vibrates with a spring effect.

The vibrations of the rod prevent the bird from settling.

MAIN ADVANTAGES

- · Very fast fitting, with silicone adhesive
- Dual-action for guaranteed results
- Discreet
- Support fitted with no grilling
- No risk for hurting the birds
- · Ideal for windowsills
- · Good value, economical

No deterioration of the support because of non-drilling

DESCRIPTION

STEELINOX® rod system (ECOPIC Product and Brand) fitted on UV-stabilised polycarbonate supports that are stuck to the surface to be protected.

www.ecopic.com

PROTECTION

· All types of edifices

 Cornices Guardrails

Gutters

Handrails

• Windowsills

To increase protection, supports can be single or double, holding one or two rods.

CABLE BIRD® has a 5 years warranty*.

S FITTING

CABLE BIRD® can be fitted to all types of supports (zinc, wood, stone...).

Very fast using silicone adhesive.

Recommendation for optimised gluing : SELFIXING® silicone adhesive.





Manual and technical data on www.ecopic.com

BIR

CITITUTUTUTU 1







www.ecopic.com

EBIRA







SACTION

Thanks to its great versatility, **SELFIXING®** silicone allows the surfaces such as aluminum, rigid PVC, glass, concrete (clean and dust-free), etc. Installation of **ECOPIC** products without using a primer on many.

S MAIN ADVANTAGES

- Appearance: Pasty
- Color: Colourless translucent
- Odour: Very faint
- Application temperature: +5 to +40 °C
- Temperature resistance : -40 to +150 °C

PROTECTION

A silicone sealant for bonding ECOPIC products. SELFIXING® is a silicone sealant recommended for the installation of ECOPIC products.

HERITAGE

S DESCRIPTION

It is a neutral silicone that can be applied cold, without primer, to: stone, concrete, zinc, etc.

SELFIXING® silicone has exceptional resistance to bad weather, particularly UV and extreme temperatures.

It is particularly suitable for making sealing and expansion joints in the building industry.

SELFIXING[®] silicone is applied using a manual or pneumatic gun to dry surfaces, free of dust, grease or other pollutants that could hinder the bonding.

Clear them if necessary with **SELCLEANING®**.

Apply a regular bead an even bead to the underside of **ECOPIC** products, then place them on the surface to be bonded by pressing lightly.

Optimum climatic conditions for installation:

• Temperatures between +5°C and +40°C, away from rain.

Support preparation:

- Cleaning with SELCLEANING®
- Dusting, degreasing, drying



RTER THAN







REF.	DESCRIPTION	PACKAGING
SIL001	Selfixing®	280 ML cartridge

INDICATION FOS USE :

- 13 to 16 linear meter / hour.
- 1 cartridge ± 10 m of ECOPIC®.

Apply to clean and dry surfaces when temperatures are between +5 and +40°C





TER THAN

υv RESISTANT

EXTREME TEMPERATURES





HIGH ADHESION



COLOURLESS

TRANSLUCENT





PREPARE THE SUPPORT



APPLY A REGULAR BEAD OF SILICONE



ecopic@ecopic.com

www.ecopic.com





CLEAN & DRY SUPPORT







EIRD[®] WIRE

R

ΥОЦ

Stretched-wire system to prevent pigeons from setting on the ledges of buildings. Recommended for low bird pressures.

HERITA

G E



E с т





Н R

Once fitted, CABLE BIRD® WIRE

with its stretch cable spring action, prevents pigeons from landing on the ledges of buildings by obstructing the area.

The vibrations of the cable prevent birds from settling.

MAIN ADVANTAGES

- · Very fast fitting, with silicone adhesive
- Dual-action for guaranteed results
- Discreet
- Support fitted with no grilling
- No risk for hurting the birds
- · Ideal for windowsills
- · Good value, economical

No deterioration of the support because of nondrilling

DESCRIPTION

System of stainless-steel cable covered with nylon and tightened by a hook (which act as a spring).

CABLE BIRD® WIRE permits the STEELINOX® hooks to flex of about 1 cm.

CABLE BIRD® WIRE has a 5 years warranty*.

S FITTING

CABLE BIRD® WIRE can be fitted to all types of support (zinc, wood, stone...).

Recommendation for optimised gluing : Polyurethane glue.





PROTECTION

· All types of edifices

 Cornices Guardrails

Gutters

Handrails

• Windowsills





EIRD[®] **WIRE**


R

HER

ΥОЦ

Н R т Е с т





G E

ΙΤΑ

🔍 CABLE BIRD® WIRE 🖻




- Product dimensions : 50 x 5 x 9 cm.
- Packaging dimensions : 23 x 19 x 12 cm box for 2,08 kg.
- Protected width : 5 to 8 cm.

One kit includes :

- · 250 polycarbonate supports, mass UV-stabilised.
- 50 double STEELINOX® hooks Ø 1,2 mm. The material used permits a high resistance, so high efficiency. Spring effect combined cable / hook.
- 2x100 m spool of nylon coated stainless steel Ø 0,7 mm.
- 400 clamps.








www.ecopic.com



BIRDWIRE

PRD YDUR HERITAGE







SACTION

Once fitted, BIRDWIRE prevents pigeons from landing on the ledges of buildings by the stretched cable's spring action.

The vibrations of the cable prevent birds from settling on it.

MAIN ADVANTAGES

- Highly-versatile-multipurpose system
 Can be fitted to almost all surfaces
- Inconspicuous
- Harmless

PROTECTION

- Ledges of buildingsRoofs
- Gutters
- · Window ledges

DESCRIPTION

System of stainless-steel cable covered with nylon and tightened by a spring held by supports attached to masonry or guttering.

FITTING

BIRDWIRE can be fitted to all types of support (wood, stone...).

. The nylon anchor rivets are fixed in masonry.







FIL

PRD

ЕСТ

YDUR

NET

Anti-bird protection system adaptable to the widest range of environmental conditions.

HERITAGE

Square-mesh anti-bird nets are designed to protect large spaces.

MAIN ADVANTAGES

- Long-lasting
- Ecological
- Inconspicuous
- Cost effective

- Sloping roofs
- Inner courtyards
- Balconies
- Metal structures or industrial premises
- Bell towers
 Trees
 Car-park interiors
- Gal-park II

Ceilings

DESCRIPTION

High-density polyethylene square-mesh nets, knotted and mass UV-stabilised.

Chemically inert, rot-proof, highlyresistant to different weather conditions and a very wide range of chemicals.

These nets are not anti-fall nets, which have different specifications.

- First make a sketch to determine the number of screw eyes and turnbuckles needed.
- Fix screw eyes every 50 cm around the perimeter and turnbuckles at corners.
- Bring the stainless-steel wire rope through the eyes and tighten it with the turnbuckles (1/10 meters).
- Fix the wire rope to the turnbuckles with u-bolts.

 Attach each mesh of the net to the wire rope with a ring (stainless-steel or aluminium staple fastened with the net stapler).

• Refer to the installation guide in each net for further details more over our team is available to help you.

For the dimensions (<25 m2) use of $\textbf{FIXNET}^{\otimes}$ recommended (consult us)

ET NE

	H [*] SHEET NE	ĒT	Starter THAN DIROS
BLACK	REF. NET109 NET103	5x5 Meters net	PAEKAGING 25 M ² 100 M ²
	NET104	20x20 Meters net	400 M ²
	NET110	10x100 Meters net	1000 M ²
STONE	NET108	5x5 Meters net	25 M ²
	NET106	10x10 Meters net	100 M ²
	NET117	20x20 Meters net	400 M ²
	NET107	10x100 Meters net	1000 M ²
TRANSLUCENT	NET123	10x10 Translucent net	100 M ²
	NET123C	10x100 Translucent net	1000 M ²
M1	NET303	10x10 Meters net**	100 M ²
	NET304	20x20 Meters net**	200 M ²
	NET310	10x100 Meters net**	1000 M ² M1 classification report on request
BLACK 19 MESI	H [*] SHEET NE		PAEKAGING
	NET111	5x5 Meters net	25 M²
	NET101	10x10 Meters net	100 M ²
	NET102	20x20 Meters net	400 M ²
	NET112	10x100 Meters net	1000 M ²
STONE	NET114	5x5 Meters net	25 M²
	NET105	10x10 Meters net	100 M²
	NET113	10x100 Meters net	1000 M ²
TRANSLUCENT	NET124	10x10 Translucent net	100 M ²
	NET124C	10x100 Translucent net	1000 M ²
M1	NET301	10x10 Meters net**	100 M ²
	NET312	10x100 Meters net**	1000 M ²
	MESURE		M1 classification report on request

ecopic@ecopic.com

-

www.ecopic.com



ecopic@ecopic.com

www.ecopic.com

Anti-bird protection system adaptable to the widest range of environmental conditions.	Shearten THAN BIRD
REP: DESERTFTER PACKAGING REP: DESERTFTER PACKAGING NET115 3 mm rope 1kg = 250 M	Black polyethylene rope for nets.
TURNEUEKLE NET016 M6 stainless-steel Unit	Eye-and-hook turnbuckles are used to tighten the wire rope.
WIRE ROPE NET007A Cable 2mm 7/7 stainless steel 50 M NET020A Cable 2mm 7/7 galvanised steel 50 M	A 2 mm 7/7 wire rope is the standar support for anti-bird nets. It combines resistance and flexibility. Stainless steel / Galvanised steel.
NET040 40 mm zinc screw eye 100 NET132 Plastic plugs (6 mm) 100	These supports can be directly screwe into wood or into masonry with a nylo plug.
CRIMP NET017 Crimp 10	The crimp are used to link the cable at tensioner.
U-BOLT NET018 Stainless-steel U-Bolt 10	U-bolts are available in stainless-steel. They are used to join lengths of wire rope.
TRUSS CLIP NET101B 3-10 mm zinc coated truss clips Unit NET101C 10-15 mm zinc coated truss clips	Allows the attachment of the cable to a metal IPN (3 - 15 mm) without drilling.
IMMEDIATE FIXING NET080 4.8 cm thread hook Unit	4.8 cm and 5.5 cm thread hook of hit in solid building materials (concrete, brick natural stone). Check the thred hook compatibility with







DESCRIPTION

Using for all mediterranean-style tiles, 'high profiled tiles'.

Possibility of using a dot of glue to optimize fixing.

The outer part of the grid adapts to various forms of tiles. Prevent the intrusion of pests while maintaining the ventilation of the roof. Easy installation (by nailing or screwing) on the fascia board.

The grid can also be installed with glue by folding the lowerpart 90°:

- 1) Seal the chimney flashings, skylights, solar panels.
- 2) Roof tiles closures, fitted on the hipes and valleys roof.

ECOPIC[®] tile products comply with all french standards requirements for ventilation of roofs (DTU 40.21, 40.22...)




















• Width : 150 mm

Single grid, installation without removable mounting clips.













Simply, highly effective bird repellent.

MAIN ADVANTAGES

- Birds are immediately scared by the movements of the balloon which simulates a real predator.
- Absolutely harmless for environment

DESCRIPTION

- Waterproof PVC conception
- 15 cm Ø
- Luminescent circles
 Bright colours
- To inflate

S FITTING

- Hang the balloon anywhere, in a visible height for birds.
- Normal use in agriculture or arboriculture : 1 balloon each 500 m².
- Industrial use : 15 balloons per hectare.
- To protect a terrace or balcony : 1 balloon.
- To be most effective, **PREDATOR**[®] needs to be installed in alternating colours each 3 weeks.



www.ecopic.com

PROTECTION

BalconiesTrees

Vegetable cropsPlay areas

• Swimming pool...



SPECIAL FOR BALCONIES



DESCRIPTIVE

PREDATOR[®] is designed in waterproof PVC, with drawings (designs) that represent the wide open mouth and piercing eyes of a predator.

Balloons move in the wind (from bottom to top, from left to right) and its metal ribbons simulate a real predator and scare the birds.

When inflated, **PREDATOR**[®] must be hang on a support or a tree in a visible height for birds. For normal use, we recommand 1 balloon each 500 m². For an industrial use, 15 balloons per Ha.

PREDATOR[®] is immediatelly effective.

Incudes three balloons : one white, one yellow, one black. Our research has shown that to be most effective, **PREDATOR**[®] needs to be installed in alternnating colors each 3 weeks.

PREDATOR[®] is absolutely harmless for environment and for birds that it scares. It is the absolute answer for agronomical environments, play areas, swimming pool, balconies, etc.






www.ecopic.com





PRDTECT YDUR HERITAGE

Adhesive anchor for bait station





S ACTION

Fixnet® Box is a cable with double sided adhesive for secure and convenient installation, that facilitate maintenance of rodent bait boxes. It is a professional accessory used for bait boxes.

Allows to fight more effectively against the profiling of rodents in a very secure way (control and filling of boxes) in accordance with regulatory standards and requirements.

MAIN ADVANTAGES

- · Economical
- · Ready to fit
- · Facilitates maintenance during treatment
- · Suitable for all bait boxes

PROTECTION

- Restaurant and community kitchens
- · Food storage areas
- · All areas frequented by rodents (interior use)

DESCRIPTION

- Highly resistant flexible cable in sheathed stainless steel. Used to fix all types of bait stations.
- · It has a loop at each end.
- · Allows a reliable, fast and precise fixing.
- Two models available :
- Fixnet® Box 60 cm (Ref: NUI023)
- Fixnet[®] Box 40 cm (Ref: NUI024)

FITTING

Apply on a suitable, clean and dry surface. Outside influences such as temperature, moisture and vandalism can influence its function / adhesive strenght.

Regulary check the correct positioning of the adhesive support during the maintenance of the bait boxes.

Insatallation : Optimun weather conditions

• Temperatures bettween +5°C and +30°C, sheltered from rain.

Preparation of the surface

- Cleaning with SELCLEANING®
- · Removal of dust, dirt and grease, drying

Simple, fast, precise fitting :

- · By gluing thanks to its integrated adhesive. · By thumb pressure, it is immediately operational.
- WARNING :

Take care not to obstruct the emergency exits when installing the Fixnet® Box.









PROTECT YOUR HERITAGE

Adhesive anchor for bait station



FIXNET® BOX ED REF. DESCRIPTION PACKAGING VUl023 Fixnet® Box Kit of 200 pieces • Adhesive anchor for bait station • Lenght 60 cm • Kit of 200 pieces cable with double sided adhesive allows strong adhesion on all type of support. • Ideal for restaurant, community and other food storage areas. • Product only intended for professional use.

🖲 FIXNET® BOX 40

REF.	DESCRIPTION	PACKAGING
NUI024	Fixnet [®] Box	Kit of 200 pieces

- Adhesive anchor for bait station
- Lenght 40 cm
- Kit of 200 pieces cable with double sided adhesive allows
- strong adhesion on all type of support.
- Ideal for restaurants and communities kitchens as well as other food storage areas.
- · Product only intended for professional use.









ZAC DU MOULIN 12 RUE DU MEUNIER 95700 ROISSY EN FRANCE - FRANCE PHONE: 488 - 78 27 40 44 FAX: 488 - 20 11 24 50

MAIL CHEOPIC @BEOPIC CON